







super Ketch" speed Ketch"

- A unique design
- For easy, fast and accurate single handed intra vascular device insertion
- Clean and Safe
- Combination of a haemostatic valve integrated push-pull button valve opener
- Cleaner and safer procedure with a minimized backflow thus limiting blood loss
- **Essential for DES**
- Perfect insertion device respecting the integrity of the coated surface
- Technical data
- Speed Ketch & Super Ketch 7F inner lumen compatibility
- 8 atm. pressure resistance after device introduction*

Ordering information

	Speed Ketch	Super Ketch	Super Ketch LSA	Torquer	Insertion Tool	Inflation device
KESU0001		20 cm side arm			Up to 0.025*	
KESU0002		20 cm side arm		0.010" to 0.035"	Up to 0.025°	
KESU0003			50 cm side arm		Up to 0.025"	
KESU0004	No side arm				Up to 0.025"	
KESU0005			50 cm sitte arm	0.010° to 0.035°	Up to 0.025"	
KESU0006	No side arm			0.010" to 0.035"	Up to 0.025"	
KISK0001		20 am sido arm		0.010" to 0.035"	Up to 0.025*	30 atm / 20 cc

(*) Haemostatic valve resistance measured in vitro, by applying injection pressure through the side port.

